

# IP68: Conquering Wind and Rain

**TB Series** 

Clip-on Thermal Imaging Attachment

#### Introduction

5

The TB Series perfectly balances precision and portability. The magnesium alloy housing decreases weight while increasing precision. The weights are over 20% lighter than those of other similar products. It is also more compact than our previous clip-on. Meanwhile, a Full-HD AMOLED display is capable, a wider viewing angle, and richer color. It is the ideal partner for relax hunting.

### **Features**

- o 12µm advanced thermal detector, NETD down to 20mK
- Full-HD 1920x1080 AMOLED display
- Magnesium alloy housing, compact design, light weight but powerful
- Two Standard 18650 batteries provides up to 12 hours of operation
- Double Side focus knob for easy operation
- Video recording including sound
- o IP68, Shock resistance up to 1000G/ms

### **Applications**

- Night Hunting
- Law Enforcement
- Search & Rescue
- Personal security





## **Specifications**







Product mode	I TB420		TB430	TB630	
Sensor					
Туре		Uncooled	VOx Infrared Detector, 8 to 14 µ	κ Infrared Detector, 8 to 14 μm	
Resolution		400×300@12µm		640×512@12µm	
NETD		25mK		20mK	
Frame rate	ie rate		50Hz		
Lens					
Objective lens	25mm, F1.0	25mm, F1.0 35mr		n, F1.0	
Field of view	10.9°×8.2°		7.8°×5.9°	12.5°×9.4°	
FOV m @100r	n 19×14		14×10	22×16	
Magnification				1x	
Detection ran	ge 1300m/ 1400yd	1300m/ 1400yd 1800m/ 1950yd			
Display					
Display type		0.39" AMOLED 1920x1080			
Color palettes	Whi	White Hot, Black Hot, Red Hot, Green Hot, Iron Red, Blue Hot, Sepia		lue Hot, Sepia	
Eyepiece	Exit pupil distance 20mm; Zo	om: 8.9x Exit pu	pil distance 20mm; Zoom: 6.4x	Exit pupil distance 20mm; Zoom: 9.5	
Hardware	I				
WIFI 2.4G, 5G					
Interface		USB Type-C (Power supply/USB2.0)			
Others		Microphone, Bluetooth			
System					
Recording fur	ction	Photo/Video (Audio recording included)			
Memory capa	city	32GB		64GB	
Power					
Battery type		2 replaceable 18650 batteries			
Operating tim	e	12 hours		10 hours	
Environmenta	 I				
Operating tem	p.	-20 °C to 50 °C/ -4°F to +122°F			
Shock	·	1000 G at 1 ms half sine pulse (as per IEC60068-2-27)			
Encapsulation		IP68			
Physical					
Weight(g/ oz)	420/ 14.82		425/ 14.99	440/ 15.52	
Size(mm/ in)		128×79×79/ 5.04×3.11×3.11			
Standard	A device, Battery charger, 186	A device, Battery charger, 18650 battery×2, 5V2A adapter (US, Britain, Australia and Europe), USB Type-C cable, Quick use guide, Warranty card			
Optional		18650 battery, Blu	Jetooth remote control, Cover ri	ng adapter	
Cover ring ad	anter				
A Weight 70 g, Compatible with 38/ 40/ 42/ 44/ 46 mm			_		
	Weight 80 g, Compatible with 48/ 50/ 52/ 54 mm		_		
D WEI		J-1 IIIII	_		

C Weight 90 g, Compatible with 56/ 58/ 60/ 62/ 64 mm